m

i



Claims

1. An optical monitoring system, comprising:

a moving body detection sub-system that images a monitored region onto an image plane and detects a moving body from changes over time in the monitored region;

a speed detection sub-system that detects a speed of the moving body in the image plane;

a scale detection sub-system that detects a size for the moving body in the image plane; and

a moving body estimation sub-system that decides whether the moving body is a predetermined monitored subject based on the speed detected by the speed detection sub-system and the size detected by the scale detection sub-system.

- 2. The monitoring system of claim 1, wherein the moving body estimation sub-system has an actual scale estimation sub-system that determines an estimated actual size of the moving body based on the speed detected by the speed detection sub-system and the size detected by the scale detection sub-system, the moving body estimation sub-system deciding whether the moving body is the predetermined monitored subject based on the estimated actual size of the moving body.
- 3. The monitoring system of claim 1, wherein the moving body estimation sub-system includes:

a correlation relationship storage sub-system that stores correlation relationships between the speed and size of predetermined classes of moving bodies; and

a class estimation sub-system that compares the speed detected by the speed detection sub-system and the size detected by the scale detection sub-system against the correlation relationships stored in the correlation relationship storage sub-system to estimate a class for the moving body, the class estimation sub-system deciding whether the moving body is the predetermined monitored subject based on the estimated class of the moving body.

m

i

ij M

[≟



- 4. The monitoring system of claim 3, wherein the correlation relationship storage sub-system stores correlation relationships between speed and size statistically obtained from previous imaging test results for each class of moving body.
- 5. The monitoring system of claim 1, wherein the moving body estimation sub-system includes a moving body evaluation sub-system that determines an evaluation value indicating a certainty that the moving body is the predetermined monitored subject based on the speed detected by the speed detection sub-system and the size detected by the scale detection subsystem, the moving body evaluation sub-system deciding whether the moving body is the predetermined monitored subject based on the evaluation value determined by the moving body evaluation sub-system.
- 6. The monitoring system of claim 1, wherein the scale detection subsystem detects a size for the moving body in only one dimension in the image plane.
- 7. The monitoring system of claim 1, wherein the scale detection subsystem detects a size for the moving body in two dimensions in the image plane.
- 8. The monitoring system of claim 7, wherein the scale detection subsystem applies different weighting factors to the two dimensions in the image plane to provide improved identification of the predetermined monitored subject.
- 9. The monitoring system of claim 7, wherein the two dimensions in the image plane correspond to horizontal and vertical directions in the monitored region, and the scale detection sub-system applies different weighting factors to the two dimensions in the image plane, with a greater weighting factor being applied to the dimension in the image plane corresponding to the vertical direction in the monitored region.
- 10. The monitoring system of claim 1, wherein the moving body detection sub-system includes a solid-state imaging element in which image signals are generated in plural pixels for each of first and second successive image frames, wherein a difference is obtained between the image signals generated in each pixel for successive first and second image frames.

m

į±

IŲ



5032497068



a moving body detection sub-system that images a monitored region onto an image plane and detects a moving body from changes over time in the monitored region;

a position detection sub-system that detects a position of the moving body in the image plane;

a scale detection sub-system that detects a size of the moving body in the image plane; and

a moving body estimation sub-system that decides whether the moving body is a predetermined monitored subject based on the position detected by the position detection sub-system and the size detected by the scale detection sub-system.

- 12. The monitoring system of claim 11, wherein the moving body estimation sub-system includes an actual scale estimation sub-system that determines an estimated actual size of the moving body based on the position detected by the position detection sub-system and the size detected by the scale detection sub-system, the actual scale estimation sub-system deciding whether the moving body is the predetermined monitored subject based on the estimated actual size of the moving body.
- 13. The monitoring system of claim 11, wherein the moving body estimation sub-system includes:

a correlation relationship storage sub-system that stores correlation relationships between the position and size of predetermined moving bodies; and

a class estimation sub-system that checks the position detected by the position detection sub-system and the size detected by the scale detection sub-system against the correlation relationships stored in the correlation relationship storage sub-system to estimate the class of the moving body and decides whether it is the predetermined monitored subject based on the estimated class of the moving body.

14. The monitoring system of claim 11, wherein the moving body estimation sub-system includes a moving body evaluation sub-system that calculates an evaluation value indicating a certainty that the moving body is

LA WA GAS TON LON

1113-014



the predetermined monitored subject based on the position detected by the position detection sub-system and the size detected by the scale detection sub-system, the moving body evaluation sub-system deciding whether the moving body is the predetermined monitored subject based on the evaluation value of the moving body evaluation sub-system.

- 15. The monitoring system of claim 11, wherein the moving body detection sub-system includes a solid-state imaging element in which image signals are generated in plural pixels for each of first and second successive image frames, wherein a difference is obtained between the image signals generated in each pixel for successive first and second image frames.
- 16. The monitoring system of any of claims 1-3, 5, and 10-13, wherein the moving body estimation sub-system decides whether a moving body is the predetermined monitored subject for a limited specified area of the monitored region.
 - 17. An optical monitoring method, comprising:

imaging a monitored region onto an image plane and detecting a moving body from changes over time in the monitored region;

detecting a speed of the moving body in the image plane;
detecting a size for the moving body in the image plane; and
deciding whether the moving body is a predetermined monitored
subject based on the detected speed in the image plane and the detected size
in the image plane.

18. The monitoring method of claim 17, further including:
determining an estimated actual size of the moving body based on the
speed detected in the image plane and the size detected in the image plane;
and

deciding whether the moving body is the predetermined monitored subject based on the estimated actual size of the moving body.

19. The monitoring method of claim 17, further including: storing correlation relationships between an image plane speed and an image plane size for predetermined classes of moving bodies;

挕

m

H []

Ĭá į÷

M

IU

M

1=

1113-014

5032497068



comparing the detected speed in the image plane and the size detected in the image plane against the stored correlation relationships to estimate a class for the moving body; and

deciding whether the moving body is the predetermined monitored subject based on the estimated class of the moving body.

20. The monitoring method of claim 17, further including:

determining an evaluation value indicating a certainty that the moving body is the predetermined monitored subject based on the speed detected in the image plane and the size detected in the image plane; and

deciding whether the moving body is the predetermined monitored subject based on the evaluation value.

- 21. The monitoring method of claim 17, further comprising deciding whether a moving body is the predetermined monitored subject only for a limited specified area of the monitored region.
 - 22. An optical monitoring method, comprising:

imaging a monitored region onto an image plane and detecting a moving body from changes over time in the monitored region;

detecting a position of the moving body in the image plane; detecting a size of the moving body in the image plane; and deciding whether the moving body is a predetermined monitored subject based on the position detected in the image plane and the size detected in the image plane.

23. The monitoring system of claim 22, further including:

determining an estimated actual size of the moving body based on the position detected in the image plane and the size detected in the image plane, and

deciding whether the moving body is the predetermined monitored subject based on the estimated actual size of the moving body.

24. The monitoring method of claim 22, further including:

storing correlation relationships between an image plane position and an Image plane size of predetermined moving bodies; and

(51 17

[] [] IJ M Ū

checking the position detected in the image plane and the size detected in the image plane against the stored correlation relationships to estimate the class of the moving body; and

deciding whether the moving body is the predetermined monitored subject based on the estimated class of the moving body.

25. The monitoring method of claim 22, further including determining an evaluation value indicating a certainty that the moving body is the predetermined monitored subject based on the position detected in the image plane and the size detected in the image plane; and

deciding whether the moving body is the predetermined monitored subject based on the evaluation value.

26. The monitoring method of claim 22, further comprising deciding whether a moving body is the predetermined monitored subject only for a limited specified area of the monitored region. .